



# MULTI-TURN ACTUATORS



200 TO 7,020 IN-LBS – NEMA 4 AND/OR 7

Indelac offers a multi-turn feature that can be installed in many of our standard quarter turn electric actuators converting them into gate and globe valve control actuators. All motors used are meeting AWWA requirements.

75% Duty Cycle					
Model	Torque		Output Speed (RPM)		Max. Number of Turns
	In-Lb	Nm	50Hz	60Hz	
SR	200	33.9	0.96	1.20	20
SX	300	33.9	0.96	1.20	20
MS	400	45.2	0.60	0.75	20
MR	675	76.3	0.40	0.50	20
ML	1,000	76.3	0.40	0.50	20
MH	1,500	169	0.10	0.13	20
LA-5	700	79.1	2.40	3.00	26
LA-12	2,000	226	0.91	1.14	26
LX-5	1,200	135	2.40	3.00	26
LX-14	3,840	434	0.84	1.05	26
5K	5,000	565	0.31	0.39	26
7K	7,020	793	0.31	0.39	26

For dimensional drawing and amp draw data please reference the chart below:

Series	Catalog Page #
S	7
M	13
L	17
K	19

For options availability please reference the chart below:

Series	2 Aux. Limit Switches	Manual Override	Power Off Brake	4-20mA Positioner	Heater	Thermostat
S	✓	✓ (Push Knob)	✓		✓	✓
M	✓	Hand Wheel Std.	✓	✓	✓	✓
L	✓	Hand Wheel Std.	✓	✓	✓	✓
K	✓	Hand Wheel Std.	✓	✓	✓	✓



*Indelac Multi-Turn Actuator with Control Panel*