



OPTIONS GRID



OPTIONS		SERIES						OPTIONS		SERIES					
		R	SD	S	M	L	K			R	SD	S	M	L	K
Enclosure	NEMA 4	Std.	Std.	Std.	Std.	Std.	Std.	Speed Control	12Vdc						
	NEMA 4X								24Vdc						
	NEMA 4 HP								24Vac						
	NEMA 6								115Vac						
	NEMA 7								230Vac						
	NEMA 4 & 7														
Motor Voltage	115 Vac	Std.	Std.	Std.	Std.	Std.	Std.	Timer	12Vdc						
	115 Vac Ext'd Duty								24Vdc						
	24 Vac								24Vac						
	24 Vdc								115Vac						
	12 Vdc							230Vac							
	208 Vac/1Ph/60Hz							Multi-Position	Three Position Vac						
	230 Vac/1Ph/60Hz								Four Position Vac						
	230 Vac/3Ph								Three Position Vdc						
460 Vac/3Ph							Four Position Vdc								
Coating	Polyester Powder	Std.	Std.	Std.	Std.	Std.	Std.	Position Indicator	Diamond Pointer						
	Exoxy Coating								Dome Style Visual Indicator	Std.	Std.		Std.	Std.	Std.
	Anodize								3 Position Dome Style Indicator						
	Fire Proof, UL-1709								Light Indication NEMA 4						
Auxiliary Switches	One								Light Indication NEMA 7						
	Two								4-20mA Transmitter						
	Three								4-20mA Transmitter High Res.						
	Four								0-10 Vdc Transmitter						Std.
	Double Pole, Double Throw														
Proximity Switches	One							Power Supply for TX & T10	115 Vac						
	Two								230 Vac						
Declutching & Man-O-Ride	Push Knob, NEMA 4								Additional Conduit Entry	1/2 NPT, NEMA 4					
	Hand Wheel, NEMA 4				Std.	Std.	Std.	1/2 NPT, NEMA 7							
	Push Knob, NEMA 7							3/4 NPT							
	Hand Wheel, NEMA 7				Std.	Std.	Std.		Special Mounting Pad	Metric tapped mounting holes					
								Special bolt pattern or drive							
								Special shaft, Slot							
Brakes, Power Off	12 Vdc							Mechanical Stop							
	24 Vdc														
	24 Vac														
	115 Vac							Temperature & Condensation Controls	Breather						
	230 Vac								Heater						
Potentiometer	1K, Single Turn, Std.							Multi-Turn	Heater & Thermostat						
	1K, Single Turn, Dual								Temperature Blanket ≥ 300°F						
	1K, 3:1 Ratio							Reversing Contractor	Without Manual Over Ride						
	1R, 0-135 Ohm								With Manual Over Ride						
	1K, Ten Turn							Transformer	Vdc						
	5K, Single Turn								3Ph						
	10K, Single Turn							Torque Sensor	3Ph						
									115 Vac					Std.	
Positioner	4-20mA 12 Vdc & 24 Vdc							Two Wire Control	12 Vdc						
	4-20mA 12 Vdc & 24 Vdc High Res.								24 Vdc						
	4-20mA 24 Vac & 115 Vac								24 Vac						
	4-20mA 115 Vac High Res.								115 Vac						
	4-20mA 230 Vac							230 Vac							
	0-135 Ohm All Voltages							Remote/Off/Local with Selector Switches	NEMA 4						
	4-20mA for Boiler Feed								NEMA 7						
	MODBUS								Open/Close Push Button						
	AS-I								Power Disconnect Switch						
									Emergency Stop Button						
							Handheld Pendant								

Available

Non-available