

# K SERIES

## SPECIFICATIONS:

Torque	Model 5K=5000 Lb-In, Model 7K=7020 Lb-In Model 12K=11520 Lb-In Model 14K=14040 Lb-In	Weight	100 Lbs.
Cycle time	68 seconds/90°	Lubrication	Permanent
Duty Cycle	Continuous	Installation	Universal
Motor	Permanent split capacitor 115Vac/1ph/50-60Hz standard With thermal over load protection	Temp. Range	-40°F. to 150°F. Heater & thermostat required 0°F. & below
L. R. Current	115Vac 5K=2.9 amps, 7K=4.1 amps 12K & 14K=7.1 amps 230Vac 5K= 1.5 amps, 7K=2.3 am 12K & 14K=3.8 amps 12Vdc 5K=4.93 amps, 7K=6.83 amps 24Vdc 5K= amps, 7K= amps	Switches	SPDT snap action 16 amp ½ HP 125, 250Vac, 0.5amp 125Vdc
Enclosure	NEMA 4 standard, NEMA 7 optional		
Coating	Thermally bonded polyester powder		
Fasteners	300 series stainless steel		
Mounting Pad	Male double "D" shaft 300 series stainless steel		
Over Ride	Manual, declutching		
Brake	Power Off, optional		
Position Ind.	Visual indicator Wired for light indication		

K Series NEMA TYPE 4

